



Amendment and Response

Applicant: John T. Ness

Serial No.: 10/629,460

Filed: July 29, 2003

Docket No.: H295.101.101

Title: CONCRETE BLOCK MOLD WITH MOVEABLE LINER

BEST AVAILABLE COPY

IN THE CLAIMS

Please cancel claims 1, 27, and 31 without prejudice.

Please amend claims 2, 3, 23, 28-30, 32, and 50 as follows:

1. (Cancelled)
2. (Currently Amended) The mold assembly of claim 43, wherein the first direction is toward a center of the mold cavity and the second direction is perpendicular to the first direction.
3. (Currently Amended) ~~The mold assembly of claim 1, wherein the gear drive assembly comprises:~~ A mold assembly for manufacturing concrete blocks and adapted for use in a concrete block machine, the mold assembly comprising:
 - a plurality of liner plates, each having a major surface, the liner plates configured such that the major surfaces form a mold cavity having a desired form; wherein at least one of the liner plates is moveable; and
 - a gear drive assembly including:
 - a first gear element having a plurality of substantially parallel angled channels and selectively coupled to the at least one movable liner plate;
 - a second gear element having a plurality of substantially parallel angled channels configured to slidably interlock with the angled channels of the first gear element; and
 - an actuator selectively coupled to the second gear element and configured to move the at least one moveable liner plate in a first direction toward an interior of the mold cavity by applying to the second gear element thea force in thea second direction, which is different from the first direction, causing the second gear element to move in the second direction and the first gear element and at least one moveable liner plate to move in the first direction toward the interior of the mold cavity, and to ~~apply to the second~~

Amendment and Response

Applicant: John T. Ness

Serial No.: 10/629,460

Filed: July 29, 2003

Docket No.: H295.101.101

Title: CONCRETE BLOCK MOLD WITH MOVEABLE LINER

~~gear element the force opposite the second direction to move the first gear~~
element and at least one moveable liner plate opposite the first direction
away from the interior of the mold cavity by applying to the second gear
element a force in a direction opposite the second direction.

4. (Original) The mold assembly of claim 3, wherein an angle of the plurality of substantially parallel angled channels ranges between forty-five degrees and ninety degrees as measured from an axis perpendicular to the major surface of the at least one moveable liner plate and extending away from an interior of the mold cavity, wherein a ninety degree angle is substantially parallel with the major surface and a zero degree angle is substantially perpendicular to the major surface.
5. (Original) The mold assembly of claim 4, wherein a preferred angle is substantially equal to seventy degrees.
6. (Original) The mold assembly of claim 3, wherein the first gear element is plate-shaped with the plurality of substantially parallel angled channels on a first major surface.
7. (Original) The mold assembly of claim 3, wherein the first gear element is substantially cylindrical in shape with the plurality of substantially parallel angled channels on a planar surface, wherein the planar surface is substantially tangentially to a radius of the cylinder.
8. (Original) The mold assembly of claim 3, wherein the second gear element is substantially cylindrical in shape with the plurality of substantially parallel angled channels on a planar surface, wherein the planar surface is substantially tangentially to a radius of the cylinder.
9. (Original) The mold assembly of claim 3, wherein the actuator is a linear actuator.

Amendment and Response

Applicant: John T. Ness

Serial No.: 10/629,460

Filed: July 29, 2003

Docket No.: H295.101.101

Title: CONCRETE BLOCK MOLD WITH MOVEABLE LINER

BEST AVAILABLE COPY

10. (Original) The mold assembly of claim 9, wherein the actuator comprises a cylinder having a piston rod selectively coupled to the second gear element.
11. (Original) The mold assembly of claim 10, wherein the cylinder is a pneumatic cylinder.
12. (Original) The mold assembly of claim 10, wherein the cylinder is a hydraulic cylinder.
13. (Original) The mold assembly of claim 10, wherein the cylinder comprises a single rod-end double-acting cylinder.
14. (Original) The mold assembly of claim 9, wherein the linear actuator comprises a threaded drive.
15. (Original) The mold assembly of claim 3, further comprising:
a mold frame having a plurality of frame members each having a major surface and
selectively coupled to one another such that the major surfaces form a mold box.
16. (Original) The mold assembly of claim 15, wherein the plurality of liner plates are located within the mold box with each liner plate corresponding to a frame member.
17. (Original) The mold assembly of claim 16, wherein the frame member corresponding to the at least one moveable liner plate includes:
a gear opening extending into the frame member from the major surface and configured to slidably receive the first gear element; and
a plurality of guide holes extending into the frame member from the major surface.
18. (Original) The mold assembly of claim 17, wherein the at least one moveable liner plate further includes a plurality of guide posts extending from a surface opposite the major surface

Amendment and Response

Applicant: John T. Ness

Serial No.: 10/629,460

Filed: July 29, 2003

Docket No.: H295.101.101

Title: CONCRETE BLOCK MOLD WITH MOVEABLE LINER

BEST AVAILABLE COPY

with one guide post corresponding to each guide hole, wherein each guide post is configured to slidably insert into the corresponding guide hole.

19. (Original) The mold assembly of claim 18, further including a plurality of guide post bushings, one inserted in each guide hole such that the guide post bushing slidably receives the corresponding guide post.

20. (Original) The mold assembly of claim 17, further comprising a gear track configured to slidably insert into the gear opening and configured to slidably receive the first gear element.

21. (Original) The mold assembly of claim 17, wherein the frame member corresponding to the at least one moveable liner further includes a gear shaft extending from an end surface of the frame member and running substantially perpendicular to and at least partially intersecting with the gear opening.

22. (Original) The mold assembly of claim 21, wherein the actuator and second gear element together form a drive unit which is configured to slidably insert into the gear shaft such that the second gear element is positioned at least partially within the gear opening.

23. (Currently Amended) The mold assembly of claim 23, further comprising a liner face selectively coupled to front surface of at least one liner plate of the plurality of liner plates, wherein the liner face comprises, at least partially, a negative a desired block shape.

24. (Original) The mold assembly of claim 23, wherein the liner face includes a negative of a pattern to be imprinted on a surface of a concrete block.

25. (Original) The mold assembly of claim 23, wherein the liner face comprises a polyurethane material.

Amendment and Response

Applicant: John T. Ness

Serial No.: 10/629,460

Filed: July 29, 2003

Docket No.: H295.101.101

Title: CONCRETE BLOCK MOLD WITH MOVEABLE LINER

BEST AVAILABLE COPY

26. (Original) The mold assembly of claim 23, wherein the liner face comprises a metal or metal alloy material.
27. (Cancelled)
28. (Currently Amended) The mold assembly of claim ~~27~~32, wherein the first direction is toward a center of the mold cavity and the second direction is perpendicular to the first direction.
29. (Currently Amended) The mold assembly of claim ~~27~~32, wherein the gear drive system is configured to simultaneously move each moveable liner plate a same distance.
30. (Currently Amended) The mold assembly of claim ~~27~~32, wherein the gear drive system is configured to simultaneously move the moveable line plates different distances.
31. (Cancelled)
32. (Currently Amended) ~~The mold assembly of claim 31, wherein each gear drive assembly comprises:~~
A mold assembly for manufacturing concrete blocks and adapted for use in a concrete block machine, the mold assembly comprising:
a mold frame comprising:
a pair of side members;
a pair of cross members selectively coupled between the side members to form a mold box; and
a plurality of division plates parallel with and between the cross members each selectively coupled between the side members to form a plurality of sub-boxes;
a pair of moveable liner plates within each sub-box, one corresponding to each side member and each having a major surface such that the major surfaces and adjacent division plates form a mold cavity within each sub-box; and

Amendment and Response

Applicant: John T. Ness

Serial No.: 10/629,460

Filed: July 29, 2003

Docket No.: H295.101.101

Title: CONCRETE BLOCK MOLD WITH MOVEABLE LINER

BEST AVAILABLE COPY

a gear drive system comprising a pair of gear drive assemblies, one associated with each side member, wherein each gear drive assembly includes:

a plurality of first gear elements, each having a plurality of substantially parallel angled channels and selectively coupled to a different one of the plurality of moveable liner plates corresponding to the associated side member;

a second gear element having a plurality of substantially parallel angled channels configured to slidably interlock with the angled channels of each of the plurality of first gear elements; and

an actuator selectively coupled to the second gear element and configured to

move each of the moveable liner plates of the associated side member in a first direction toward an interior of the mold cavity by applying to the second gear element the force in the second direction, which is different from the first direction, causing the second gear element and each first gear element and corresponding liner plate to move in the first direction toward the interior of the corresponding mold cavity, and to move each of the moveable liner plates of the associated side member opposite the first direction away from the interior of the corresponding mold cavity by applying to the second gear element the force in a direction opposite the second direction-causing each first gear elements and corresponding liner plate to move away from the interior of the corresponding mold cavity.

33. (Original) The mold assembly of claim 32, wherein the second gear element comprises a plurality of groups of substantially parallel angled channels, each group of angled channels corresponding to and configured to slidably interlock with the angled channels of a different one of the first gear elements of the plurality of first gear elements.

34. (Original) The mold assembly of claim 33, wherein an angle of the plurality of substantially parallel angled channels ranges between forty-five degrees and ninety degrees as measured from an axis perpendicular to the major surface of the liner plate and extending away

Amendment and Response

Applicant: John T. Ness

Serial No.: 10/629,460

Filed: July 29, 2003

Docket No.: H295.101.101

Title: CONCRETE BLOCK MOLD WITH MOVEABLE LINER

from the interior of the mold cavity, wherein a ninety degree angle is substantially parallel with the major surface and a zero degree angle is substantially perpendicular to the major surface.

35. (Original) The mold assembly of claim 34, wherein a preferred angle is substantially equal to seventy degrees.

36. (Original) The mold assembly of claim 34, wherein the angle of the substantially parallel angled channels of each group of the second gear element is substantially equal to the angle of the substantially parallel angled channels of its corresponding first gear element and wherein the angle of the substantially parallel angled channels varies from group to group such that the moveable liner plates will move a different distance toward the interior of the correspond mold cavity in response to the second force being applied to the second gear element.

37. (Original) The mold assembly of claim 32, wherein each first gear element is a rectangular plate with the plurality of angled channels on a first major surface.

38. (Original) The mold assembly of claim 32, wherein each first gear element is substantially cylindrical with the plurality of substantially parallel angled channels on a planar surface, wherein the planar surface is substantially tangential to a radius of the cylindrical.

39. (Original) The mold assembly of claim 32, wherein the second gear element is substantially cylindrical with the plurality of substantially parallel angled channels on a planar surface, wherein the planar surface is substantially tangential to a radius of the cylindrical.

40. (Original) The mold assembly of claim 32, wherein the actuator is a linear actuator.

41. (Original) The mold assembly of claim 40, wherein the actuator comprises a piston having a piston rod selectively coupled to the second gear element.

Amendment and Response

Applicant: John T. Ness

Serial No.: 10/629,460

Filed: July 29, 2003

Docket No.: H295.101.101

Title: CONCRETE BLOCK MOLD WITH MOVEABLE LINER

42. (Original) The mold assembly of claim 41, wherein the piston is a hydraulic piston.
43. (Original) The mold assembly of claim 41, wherein the piston is a pneumatic piston.
44. (Original) The mold assembly of claim 40, wherein the actuator comprises a threaded drive.
45. (Original) The mold assembly of claim 32, wherein each side member includes a plurality of gear openings, one associated with each sub-box and each configured to slidably receive a first gear element of a corresponding moveable liner plate.
46. (Original) The mold assembly of claim 45, further including a plurality of gear tracks each configured to slidably insert into a different one of the plurality of gear openings and configured to slidably receive a first gear element.
47. (Original) The mold assembly of claim 32, wherein each side member includes a plurality of guide holes associated with each sub-box.
48. (Original) The mold assembly of claim 47, wherein the pair of moveable liner plates associated with each sub-box each have a plurality of guide posts extending from a surface opposite the major surface, wherein each guide post is configured to slidably insert into a different one of the plurality of guide holes.
49. (Original) The mold assembly of claim 48, further comprising a plurality of guide post bushings, one inserted into each of the plurality of guide holes and configured to slidably receive a corresponding guide post.
50. (Currently Amended) The mold assembly of claim ~~27~~32, further comprising a liner face selectively coupled to the major surface of at least one of the moveable liner plates.

Amendment and Response

Applicant: John T. Ness

Serial No.: 10/629,460

Filed: July 29, 2003

Docket No.: H295.101.101

Title: CONCRETE BLOCK MOLD WITH MOVEABLE LINER

51. (Original) The mold assembly of claim 50, wherein the liner face comprises, at least partially, a negative of a desired block shape.

52. (Original) The mold assembly of claim 50, wherein the liner face comprises a negative of a desired pattern to be imprinted on a surface of a concrete block.

53. (Original) The mold assembly of claim 50, wherein the liner face comprises a polyurethane material.

54. (Original) The mold assembly of claim 50, wherein the liner face comprises a metal alloy.

55.-67. (Withdrawn)